

## ATOLL®

### Protective gloves

Made of seamless nylon knitted fabric in green colour providing comfort while wearing (13g).

The palm and finger tips are double-coated with nitrile (with "sandy finish") in black which guarantees excellent grip.

The back is not coated what increases comfort of usage.

The gripping part features high abrasive resistance what extends lifeperiod of the gloves.

The gloves are dedicated for work performed in damp and oily environment requiring good gripping capacity, precision and high resistance to abrasion. They are used, among others, in performing precise assembly work or in metal processing, especially recommended for warehouses and building sites.

They are provided with elastic welt finished with coloured thread used for size identification.

The gloves meet general requirements for personal protective equipment provided in Regulation (EU) 2016/425 and in the Harmonised Standards: EN 388 and EN ISO 21420.



### Technical Information:

Material: nylon knitted fabric coated with nitrile („sandy finish“)

Performance level: 4121X

Sizes: 8, 9, 10, 11

Order numbers: R-I-ATOLL-XX\*

\*insert size for XX

### EN 388 Protective gloves against mechanical risks



*Performance level	1	2	3	4	5	
Resistance to abrasion / cycles	100	500	2000	<b>8000</b>	-	
Cut resistance / index	<b>1,2</b>	2,5	5	10	20	
Tear strength [N]	10	<b>25</b>	50	75	-	
Puncture resistance [N]	<b>20</b>	60	100	150	-	
	A	B	C	D	E	F
Cut resistance (TDM) [N]	2	5	10	15	22	30

The letter X means that test was not performed



4121X