

AXSTONE® MAX

Cut resistant gloves

Made of UHMWPE and glass fibre (13g). The palm is coated with polyurethane in grey colour. The back is not coated, what increases comfort of usage.

Labelling in red color on the label inside gloves signals high level of cut resistance (D).

They feature high abrasion (4) and tear (4) resistance, which extends the life period of the gloves.
They offer good dexterity, while at the same time maintaining high performance level.

Due to high cut resistance level, these gloves are a perfect choice for work with sharp objects where high dexterity is required, for instance managing the steel plate edges and glass, e.g. in an automotive industry.

They are provided with elastic welt finished with coloured thread used for size identification.

The gloves meet general requirements for personal protective equipment provided in Regulation (EU) 2016/425 and in the Harmonized Standards:
EN ISO 21420 and EN 388.

Technical Information:

Material:	UHMWPE yarn and glass fibre coated with polyurethane
Performance level:	4X43D
Sizes:	8, 9, 10, 11
Order numbers:	R-I-AXSTONEMAX-XX*

*insert size for XX

Size identification by variously coloured cuff

8 9

10 11

EN 388 Protective gloves against mechanical risks

EN 388

4X43D*

*Performance level	1	2	3	4	5
Resistance to abrasion / cycles	100	500	2000	**8000**	-
Cut resistance / index	1,2	2,5	5	10	20
Tear strength [N]	10	25	50	**75**	-
Puncture resistance [N]	20	60	**100**	150	-
	A	B	C	D	E	F
Cut resistance (TDM) [N]	2	5	10	**15**	22	30

The letter X means that the test was not preformed.

120 12

EN 388

4X43D

Marking of a cut resistance performance level (in accordance with EN 388):

4	X	4	3	D