

AXSTONE®

Cut resistant gloves

Made of UHMWPE (13g).
The palm is coated with polyurethane in grey colour.
The back is not coated, what increases comfort of usage.

Labelling in green color on the label inside gloves signals 4th level of cut resistance.

They feature high abrasion (4) and tear (4) resistance, which extends the life period of the gloves.
They offer good dexterity, while at the same time maintaining high performance levels.


Due to a high cut resistance level, the gloves are a perfect choice for work with sharp objects where high dexterity is required, for instance managing steel plate edges and glass, e.g. in an automotive industry.

They are provided with elastic welt finished with coloured thread used for size identification.

The gloves meet general requirements for personal protective equipment provided in Regulation (EU) 2016/425 and in the Harmonized Standards: EN ISO 21420 and EN 388.



Size identification by variously coloured cuff ribbing:



Technical Information:

Material:	UHMWPE yarn coated with polyurethane
Performance level:	4443B
Sizes:	6, 7, 8, 9, 10, 11
Order numbers:	R-I-AXSTONE-XX*

*insert size for XX

EN 388 Protective gloves against mechanical risks

*Performance level	1	2	3	4	5
EN 388 Resistance to abrasion / cycles	100	500	2000	8000	-
Cut resistance / index	1,2	2,5	5	10	20
Tear strength [N]	10	25	50	75	-
Puncture resistance [N]	20	60	100	150	-
	A	B	C	D	E
Cut resistance (TDM) [N]	2	5	10	15	22
	F				30



The letter X means that the test was not performed.

Marking of a cut resistance performance level (in accordance with EN 388):

