

### Intended Use:

The ANTYSTAT PETROLEUM model protective clothing (see Table no 1 for a detailed list of clothing models) is designed to be used in an environment which requires the ability to dissipate electrostatic discharges able to initiate ignition. The clothing is designed to be worn in zones: 1, 2, 20, 21 and 22 (see EN 60079-10-1 and EN 60079-10-2) where the minimum ignition energy of the explosive atmosphere is not lower than 0.016 mJ.

**Composition:** 65% polyester, 34% cotton, 1% carbon fibre.

The product conforms to the relevant requirements of the EU harmonisation legislation: Regulation (EU) 2016/425 and the harmonised standards: EN ISO 13688:2013, EN 1149-5:2018. The declaration of conformity is available on the website [www.robod.pl/ce](http://www.robod.pl/ce)



EN 1149-5:2018

1

2

3

### Explanation of graphic characters:

1. The clothing conforms to the relevant requirements of the EU harmonisation legislation: Regulation (EU) 2016/425.
2. Protective electrostatic dissipative clothing.
3. Make yourself familiar with these instructions before use.


### Use:

Select the clothing size to fit the user based on the sizes presented on the label attached to the product. The protective electrostatic dissipative jacket should be used together with the protective electrostatic dissipative trousers (protective bib and brace overalls or protective waist high trousers). The clothing should always cover the body, shoulders and legs. The protective electrostatic dissipative vest should be used together with the protective electrostatic dissipative clothing set, i.e. with the jacket and the protective bib and brace overalls or protective waist high trousers. The clothing should always cover the body, shoulders and legs. Always make sure the clothing is accurately fastened or buttoned up when being used. The protective electrostatic dissipative clothing should neither be unzipped or unbuttoned nor taken off in the presence of flammable or explosive atmospheres or while working with flammable or explosive substances. It is forbidden to clean, wipe, sweep, dust etc. the clothing in the presence of flammable or explosive atmospheres or while working with flammable or explosive substances. Carry out all cleaning and maintenance operations outside the hazard zone. A person wearing the protective electrostatic dissipative clothing should be properly earthed e.g. by wearing appropriate footwear on a dissipative or conductive substrate. The electric resistance between the human skin and the ground should be less than  $10^8 \Omega$ . Visually inspect the clothing for damages before each usage. Damaged, e.g. torn, ripped etc. clothing should be immediately withdrawn from use. The protective electrostatic dissipative clothing should be worn so as to permanently cover up all materials not fulfilling the requirements while doing the everyday work (also while bending, leaning etc.). In case when works are done in leaning positions, the protective blouse must properly cover the upper part of the protective trousers. In the presence of flammable or explosive atmospheres or while working with flammable or explosive substances, you must not hook up to the brackets nor store in the pockets with which the clothing is equipped any protruding objects which have not been approved for use under such hazards.

### Transportation and Storage:

Store the clothing in its genuine packaging. The clothing should be stored in a dry and well ventilated room far from sources of heat and light, protected against getting soiled, stained and damaged and from the impact of chemicals. Do not store the clothing for more than 5 years following the date of purchase. Prevent it from getting heavily soiled and stained.

### Cleaning and Maintenance:



Maximum number of maintenance cycles - 50.

1. Maximum washing temperature: 60 deg. C.
2. Do not use bleaching.
3. Tumble drying possible. Drying at lower temperature. Maximum exhaust temp. 60deg. C.
4. Maximum temperature of iron sole plate: 150 deg. C.
5. Professional dry cleaning in tetrachloroethylene and all solvents listed for the F symbol.

### Disposal:

Dispose in conformity to the local regulations mandatory in the given country.

### Note:

- ① The protective electrostatic dissipative clothing should not be used in flammable atmospheres enriched with oxygen or in zone 0 (see EN 60079-10-1 and EN 60079-10-2) without an earlier approval of an engineer responsible for safety.
- ① The efficiency of protection provided by the protective electrostatic dissipative clothing may be affected by: its wear, damages, tears, washing and potential soiling.
- ① The protective electrostatic dissipative clothing does not provide protection against the impact of flame and hot factors.
- ① Do not use the protective electrostatic dissipative clothing for protection against electric shock.
- ① The materials used to manufacture the ANTYSTAT PETROLEUM model protective clothing has not been found to contain substances likely to cause allergic reactions although in case an allergic reaction is shown, particularly by sensitive persons, they must leave the hazard zone, take off the clothing and consult a doctor.
- ① We recommend keeping these instructions.

### This usage manual is applicable to the following clothing models:

#### Protective anti-static insulated jacket (1)

model: ANTYSTAT PETROLEUM

#### Protective anti-static insulated bib-and-brace overalls (2),

model: ANTYSTAT PETROLEUM

#### Protective antistatic insulated waist high trousers (3)

model: ANTYSTAT PETROLEUM

*To ensure the required level of protection, the protective anti-static jacket (1) must be used together with the protective anti-static overalls or trousers.  
The protective antistatic vest must only be used together with the protective anti-static clothing set, i.e. with the jacket and the protective bib and brace overalls or protective waist high trousers.  
Table no 1*

ROBOD S.A.  
80-017 Gdańsk, Poland  
Trakt św. Wojciecha 223/225  
Tel. (+48) 58 321 98 20  
e-mail: [info@robod.pl](mailto:info@robod.pl)  
[www.robod.pl](http://www.robod.pl)

The EU type assessment certificate was issued by the notified body: Textile Research Institute (no 1435), 92-103 Łódź, Poland, ul. Brzezińska 5/15.